



1. PERFORMANCE


- 1) Measuring range : 0.01-0.6 %
- Number of pump strokes : 1 (100mℓ)
- 2) Sampling time : 1 minute/1 pump stroke
- 3) Detectable limit : 0.005 % (50 ppm)
- 4) Shelf life : 3 years
- 5) Operating temperature : 10 ~ 40 °C
- 6) Temperature compensation : Necessary (See "TEMPERATURE CORRECTION TABLE")
- 7) Reading : Direct reading from the scale calibrated by 1 pump stroke
- 8) Colour change : Orange → Dark green

2. RELATIVE STANDARD DEVIATION

RSD-low : 10 % RSD-mid. : 5 % RSD-high : 5 %

3. CHEMICAL REACTION

Chromium oxide is reduced.





4. CALIBRATION OF THE TUBE

GAS CHROMATOGRAPHY

5. INTERFERENCE AND CROSS SENSITIVITY

| Substance | Interference | ppm | Coexistence |
|----------------------------------------------------|-------------------------------------------|-------|----------------------------|
| Benzene FIG.1 | Black stain is produced. | 400 | Higher readings are given. |
| Toluene FIG.2 | ∕ | 800 | ∕ |
| Xylene | ∕ | 2,000 | ∕ |
| Acetylene | Whole layer is discoloured to Dark green. | | ∕ |
| Ethylene | Similar stain is produced. | | ∕ |
| Aliphatic hydrocarbons (more than C ₃) | ∕ | | ∕ |

* In presence of Alcohols, Ketones or Esters less than 6 %, the accuracy of readings is not affected.



TEMPERATURE CORRECTION TABLE

| Tube Readings (%) | Corrected Concentration (%) | | | | |
|-------------------|-----------------------------|---------------|---------------|---------------|----------------|
| | 10 °C (50 °F) | 15 °C (59 °F) | 20 °C (68 °F) | 30 °C (86 °F) | 40 °C (104 °F) |
| 0.6 | 0.73 | 0.67 | 0.60 | 0.53 | 0.49 |
| 0.5 | 0.62 | 0.54 | 0.50 | 0.45 | 0.41 |
| 0.4 | 0.48 | 0.43 | 0.40 | 0.36 | 0.34 |
| 0.3 | 0.34 | 0.32 | 0.30 | 0.28 | 0.26 |
| 0.2 | 0.22 | 0.21 | 0.20 | 0.19 | 0.18 |
| 0.1 | 0.10 | 0.10 | 0.10 | 0.10 | 0.10 |